

	2024 Product Guide					
	Northeast Pro-Series	Slocomb Harmony 100	Slocomb Protech 400	United 9600 series	Trimline DR200	Andersen 400 Woodwright
	Sturdy and well designed	Sleek design together	Hurricane rated DP 50	This window replicates the look	For the purist, this	Andersen is a best-seller and
	Nice Asthetics	with rugged engineering	Sturdy and well designed	of a wood window	wood window offers the	is second to none.
	heavy duty extruded	make this the best	InnergyTM Rigid	with a durable design featuring a	closest thing to the	Used for historic and traditional homes.
	screen frame	looking & durable	Thermal Reinforcement:	welded vinyl frame and a	original wood window	Natural wood interior
		performer		solid core cellular PVC sash	it is to replace	Patented Fibrex exterior
				for a timeless visual appeal		
Grade	Structural Grade Rating DP 40	Structural Grade Rating DP 35	Structural Grade Rating DP 50	Performance Class LCPG40-H	Structural Grade Rating DP LC 45	Insert style frame DP 25
			Light Commercial rated	Light Commercial rated	Light Commercial rated	Full (new construction) DP 50
Frame	Welded PVC	Welded multi chambered PVC	Welded multi chambered PVC	Composite window	dovetailed pine	dovetailed pine
	multi-chambered	multi chambered PVC	InnergyTM Rigid	welded vinyl frame and a	corners with	corners with
		Integral ant-bow sill interlock	Thermal Reinforcement	solid core cellular PVC sash	aluminum clad	Fibrex Clad exterior
			magnetic bottom seal			
Glass	7/8" double pane	3/4" double pane	7/8" double pane	3/4" double pane	7/8" double pane	5/8" double pane
	Low E/Argon Gas	Low E/Argon Gas	Low E/Argon Gas	Low E2/Argon Gas	Low E/Argon Gas	Low E/Argon Gas
		Duralite high efficiency spacer				
	PPG Intercept Spacer	Duralite high efficiency spacer Improved condensation resistance Superior argon gas retention Unique patented design Exceeds ENERGY STAR	Duralite high efficiency spacer Improved condensation resistance Superior argon gas retention Unique patented design Exceeds ENERGY STAR	High performance Stainless Steel Intercept Spacer Exceeds ENERGY STAR	Super spacer dual seal technology - acrylic seal with a barrier seal Comfort Plus technolgy Balanced year round performance Exceeds ENERGY STAR	High performance Stainless Steel spacer Exceeds ENERGY STAR
Balance System	constant force	constant force	constant force	constant force	block & tackle	block & tackle
Grids (optional) inside glass	5/8" contour grids	5/8" contour grids	5/8" contour grids	5/8" contour inside glass or simulated divided lites	5/8" contour inside glass or simulated divided lites	Up to 9 hardware finish options custom grille patterns
Screen	Extruded alum frame - fiberglass mesh	Extruded alum frame - fiberglass mesh	Extruded alum frame fiberglass mesh	Roll form fiberglass mesh	Extruded alum frame - fiberglass mesh	Extruded alum frame - fiberglass mesh
Warranty	life frame- 20 yrs Glass	lifetime - transferable	lifetime - transferable	lifetime - transferable	10yrs-frame/20-glass	10yrs-frame/20-glass
	Non Transferable	Non Pro rated and Transferable	Non Pro rated and Transferable	Non Pro rated and Transferable	Transferable	Transferable
		Good Housekeeping Seal & Warranty	Good Housekeeping Seal & Warranty			
options:	bright white	soft white & almond	soft white & almond	Soft white	pre- painted interior	pre- painted interior
Colors:		10 exterior colors	Exterior Laminate colors:	Black co-extruded inside & out	Exterior colors:	7 exterior colors
		Available	Black - bronze	Black ext.(painted) w/white interior	White - Beige - Brown	with 3 natural wood interiors
		All Painted	Plus10 colors w/painted exterior		Black - Green	
Energy efficiency	U Value = .30	U Value = .27	U Value = .26	U Value = U.27	U Value =.30 Comfort E -.27 Comfort e Plus	U Value = U.27
Min - max sizes	w 15.25"-53" h-23.75"-86"	w -14.25"-54" h - 20.5 -85 max 124ui	W-12.75 - 58" h- 20 - 106 max 140	W - 19 3/4" - 48" H- 25.25" - 80"	w -14"-48" h - 24 -84 max 132ui	w 16.5"-45.5" h 32"-76.875"